

6

5

4

3

2

1

F

E

D

C

B

A

F

E




D

C

B

A

REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	B	ECO-16036	07/21/2026	DMAY	DGUST



NOTES:

- MATERIAL: RED PVC.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

6

5

4

3

2

1

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS		Show Me[™] CABLES an INFINIT® company Website: www.ShowMeCables.com Phone: 1.888.519.9505		 INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5			
				TOLERANCES:		SCALE	SHEET
				.X = ±.2 [5]	FRACTIONS ± 1/32	NONE	1 OF 1
.XX = ±.02 [0.5]	ANGLES ± 1°						
.XXX = ±.005 [0.13]							
CABLE LENGTH TOLERANCES:							
≤12 [305] = +1 [25] / -0							
>12 [305] ≤ 60 [1524] = +2 [51] / -0							
>60 [1524] ≤ 120 [3048] = +4 [102] / -0							
>120 [3048] ≤ 300 [7620] = +6 [152] / -0							
>300 [7620] = +5% / -0							
CABLE LENGTH TOL IAW IPC A-620							
ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE. UN-DIMENSIONED/NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION COLORS MAY VARY		DESCRIPTION					
		RJ45 STRAIN RELIEF BOOT - RED					
SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV			
A	3SVT8	DMAY	1436	B			