

6

5

4


3

2

1

## REVISION


ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	B	ECO-15142	01/29/2026	TDUFRENE	DGUST




1. HD15 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR
2. DC 3.5 STEREO PLUG
3. MOLDED THUMBSCREW #4-40, LENGTH 49mm, BLACK
4. UL{[28AWG+AL+S(29/0.10mmTS)]\*3COAXIAL+(28AWG\*4.5P)+28AWG\*3C}, AL+D#+AMA, BRAID(47%), OD:9.2mm, JACKET BLACK
5. UL2464 3C 28AWG, ALUM-MYLAR FOIL SHIELD WITH DRAIN WIRE, OD 3.5mm, JACKET BLACK
6. MOLDED PVC BLACK  
MOLDED PE COLOR TRANSPARENT  
ALUMINUM FOIL 17\*65mm  
BLACK HEAT SHRINK TUBE Ø1.0\*10mm  
BLACK HEAT SHRINK TUBE Ø3.0\*10mm  
BLACK PVC TUBE Ø3.0\*22mm
7. MOLDED PVC BLACK
8. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY
9. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

## WIRING MAP



## WIRING MAP



UNLESS OTHERWISE SPECIFIED  
LEADING DIMENSIONS ARE INCHES  
DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:  
X = ±.2 [5] FRACTIONS  
.XX = ±.02 [0.5] ± 1/32  
.XXX = ±.005 [0.13] ANGLES ± 1°


CABLE LENGTH TOLERANCES:  
≤12 [305] = +1 [25] / -0  
>12 [305] ≤ 60 [1524] = +2 [51] / -0  
>60 [1524] ≤ 120 [3048] = +4 [102] / -0  
>120 [3048] ≤ 300 [7620] = +6 [152] / -0  
>300 [7620] = +5% / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY  
AND SUBJECT TO CHANGE WITHOUT NOTICE  
UN-DIMENSIONED/NON-CRITICAL FEATURES  
MAY VARY IN SIZE AND LOCATION  
COLORS MAY VARY

**Show Me**  
CABLES

an INFINIT® brand

Website: [www.ShowMeCables.com](http://www.ShowMeCables.com)  
Phone: 1.888.519.9505



INTERPRET ALL DIMENSIONS AND  
TOLERANCES PER ASME Y14.5

SCALE NONE SHEET 1 OF 1

DESCRIPTION  
VGA MONITOR CABLE MALE/MALE WITH 3.5MM STEREO

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	3SVT8	TDUFRENE	43-116-XXX	B

6

5

4

3

2

1