

### 10/100 Mbps Singlemode Fiber Optic Ethernet Media Converter- SC-20Km

Part No: 47-400-020

#### MEDIA CONVERTER & MODULE

Standards and Protocols	IEEE 802.3, IEEE 802.3u, IEEE802.3x
Basic Function	Half/Full- Duplex transfer mode for FX port Full Duplex Flow Control (IEEE 802.3x) Half Duplex Flow Control (Backpressure) Extends fiber distance up to 20km Link Fault Passthrough and Far end Fault minimize the loss caused by link failure timely
Ports	1 100M SC/UPC port 1 100M RJ45 port (Auto MDI/MDIX)
Wave Length	1310nm
Network Media 10BASE-T	UTP category 3,4,5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Network Media 100BASE-T	UTP category 5,5e cable (maximum 100m) EIA/TIA-568 100Ω STP )maximum 100m)
Network Media 100BASE-FX	Single-mode Fiber
LED Indicators	PWR,FDX/Col, Link/Act, SPD
Dimensions (W*D*H)	3.7*2.9*1.1 in. (94.5*73.0*27.0 mm)
Power Supply	External power supply
Max Power Consumption	1.52W
Safety & Emission	FCC, CE, RoHS
Environment	Operating Temperature:0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C(-40°F~158°F) Operating Humidity: 10%-90% non-condensing Storage Humidity: 5%-90% non-condensing