

6

5

4

3

2

1

REVISION

| ZONE | REV | DESCRIPTION | DATE | CHANGED BY | APPROVED |
|------|-----|-------------|------------|------------|----------|
| | B | ECO-13650 | 06/17/2024 | DZINN | DGUST |

F

E

D

C

B

A

F


E

D

C

B

A



WIRING MAP

| P1 | P2 |
|-------------------|-----|
| 1 ----- RED ----- | (+) |
| 4 ----- BLK ----- | (-) |

NOTES:

- MATERIAL:
CABLE: 24 AWG, 2 CONDUCTORS,
PVC JACKET OD: .138 ±.006 [3.5 ±0.15]
MARKING: AWM 2464 80°C 300V 24AWG*2C VW-1
P1 PLUG: USB-A MALE, NICKEL PLATED SHELL,
INSULATOR COLOR: WHITE
MOLDED PVC BOOT.
P2 PLUG: DC Ø4.0 X 1.7 mm MALE, NICKEL PLATED SHELL,
INSULATOR COLOR: BLACK
MOLDED PVC BOOT.
- ELECTRICAL TEST:
100% OPEN SHORT AND MISS WIRE TEST.
CONDUCTIVE RESISTANCE: 0.2 Ω MAX.
INSULATION RESISTANCE: 10 MΩ MIN AT 300V DC.

REGULATORY COMPLIANCE:
EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION).

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

6

5

4

3

2

1

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

| | |
|---------------------|---------------------|
| X = ±.2 [5] | FRACTIONS ± 1/32 |
| .XX = ±.02 [0.5] | ANGLES ± 1° |
| .XXX = ±.005 [0.13] | |

CABLE LENGTH TOLERANCES:

| | |
|--------------------------|-----------------|
| ≤12 [305] | = +1 [25] / -0 |
| >12 [305] ≤ 60 [1524] | = +2 [51] / -0 |
| >60 [1524] ≤ 120 [3048] | = +4 [102] / -0 |
| >120 [3048] ≤ 300 [7620] | = +6 [152] / -0 |
| >300 [7620] | = +5% / -0 |

ALL DIMENSIONS ARE FOR REFERENCE ONLY
AND SUBJECT TO CHANGE WITHOUT NOTICE.
UN-DIMENSIONED/NON-CRITICAL FEATURES
MAY VARY IN SIZE AND LOCATION
COLORS MAY VARY

Show Me
CABLES

an INFINIT® brand

Website: www.ShowMeCables.com
Phone: 1.888.519.9505



INTERPRET ALL DIMENSIONS AND
TOLERANCES PER ASME Y14.5

| | |
|---------------|-----------------|
| SCALE NONE | SHEET 1 OF 1 |
|---------------|-----------------|

DESCRIPTION

DC CA, USB to 4.0mm/1.7mm M, 3 FT

| SIZE | CAGE CODE | DRAWN BY | ITEM NO. | REV |
|------|-----------|------------|------------|-----|
| A | 3SVT8 | AKRESOWSKI | 55-171-XXX | B |