

6

5

4

3

2

1

REVISION

ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	09/19/2024	HBAKKE	GUTTADAURO

"P1"

PIN 1

LENGTH

"P2"

PIN 1

2X RJ45 SHIELDED PLUG
GOLD PLATED CONTACTS


2X SNAGLESS BOOT
LSZH, BLACK

CAT 7 SHIELDED MODULAR CABLE
FOUR TWISTED PAIR, WITH ALUMINUM/ POLYESTER FOIL SHIELDING OF EACH PAIR
CONDUCTORS: 26 AWG STRANDED COPPER
OVERALL SHIELD: TINNED COPPER BRAID
JACKET: LOW SMOKE ZERO HALOGEN, COLOR: BLACK, NOM DIA. .236" [6.0mm]
(OPERATING TEMPERATURE: -10°C~+80°C; VOLTAGE RATING: 30V)

WIRING MAP

P1

P2



SHIELD

SHIELD

NOTES:

1. LSZH CABLE CHARACTERISTICS:
FLAME RATING: IEC 60332-1
CORROSIVE GAS: IEC 60754
SMOKE EMISSION: IEC 61034
LENGTHS OVER 10 METERS (32.8 FT) ARE CHANNEL RATED.
PLUG CONFORMS TO TIA-1096.
- 2.
- 3.
4. CABLE ASSEMBLY TO BE TESTED FOR CONTINUITY.
5. CABLE ASSEMBLY TO BE INDIVIDUALLY PACKAGED.

PART NUMBER	LENGTH	
	METERS	FEET
726Z-0.5 BK	0.5	1.64
726Z-01 BK	1.0	3.28
726Z-02 BK	2.0	6.56
726Z-03 BK	3.0	9.84
726Z-05 BK	5.0	16.40
726Z-7.5 BK	7.5	24.61
726Z-10 BK	10.0	32.81
726Z-15 BK	15.0	49.21

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS


TOLERANCES:
X = ±.2 [5] FRACTIONS
.XX = ±.02 [0.5] ± 1/32
.XXX = ±.005 [0.13] ANGLES ± 1°

CABLE LENGTH TOLERANCES:
≤12 [305] = +1 [25] / -0
>12 [305] ≤ 60 [1524] = +2 [51] / -0
>60 [1524] ≤ 120 [3048] = +4 [102] / -0
>120 [3048] ≤ 300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY
AND SUBJECT TO CHANGE WITHOUT NOTICE.
UN-DIMENSIONED/NON-CRITICAL FEATURES
MAY VARY IN SIZE AND LOCATION
COLORS MAY VARY

Show Me
CABLES
an INFINIT® brand

Website: www.ShowMeCables.com
Phone: 1.888.519.9505



INTERPRET ALL DIMENSIONS AND
TOLERANCES PER ASME Y14.5

SCALE SHEET
NONE 1 OF 1

DESCRIPTION

CAT 7 10GIG, S/FTP, 26AWG STR, LSZH, BLK

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

6

5

4

3

2

1