

Closet Connector Housing (CCH)

2 rack units, holds 4 CCH connector panels

CORNING

Designed based on thousands of hours of customer feedback, Corning Cable Systems Closet Connector Housings (CCHs) offer more than two dozen innovative features that make installation and troubleshooting of fiber optic connectivity faster, easier and more cost effective.

From fiber and cable routing and strain relief, to port labeling and termination, these housings reduce the risk of error that can disrupt networks.

Closet Connector Housings (CCHs) provide interconnect or cross-connect capabilities between outside plant, riser or distribution cables and opto-electronics. Like all LANscape Solutions hardware, the housings accept CCH connector panels. In addition, the housings accept CCH cassettes and CCH modules.

The units are designed for rack mounting in 19-in (48 cm) racks or optional 23-in (58 cm) equipment racks (1.75-in EIA hole spacing). They are available in rack space options of 1U (two panels, cassettes or modules), 2U (four panels, cassettes or modules), 3U (six panels, cassettes or modules) and 4U (twelve panels, cassettes or modules). The 1U, 2U and 3U options feature a slide-out tray and see-through, removable top covers. The CCH-04U features a clear door, removable front and rear enclosures and a platinum-painted interior for maximum visibility and access.

Every CCH housing is shipped complete with strain relief brackets, routing clips and guides, and mounting brackets for proper installation. Documentation labels are provided and components can be added as needed to construct a fiber distribution frame for any application. All housings include a removable tinted polycarbonate front door. All size housings have field-installable lock kits available for both front and rear doors.

All CCH housings can also be upgraded for pigtail splicing to full fiber capacity and easy, modular fiber management through the use of CCH Splice Cassettes (CCH-CS), or for easy, modular fiber management when using field-installable connectors through the use of CCH Slack Cassettes (CCH-CF).



Features and Benefits

Interconnect and cross-connect capability

Ideal for field connectorization

Removable, translucent top covers (1U, 2U, 3U), removable rear cover (4U)

Visibility and ease of access for installation, testing and troubleshooting

Closet Connector Housing (CCH)

2 rack units, holds 4 CCH connector panels



Features and Benefits

Internal and external strain-relief options

Flexibility for installation and moves, adds and changes (MACs)

Accepts panels, modules and cassettes

Variety of field termination options

Adaptable to use as a modular splice housing

Splices are stored and protected in same footprint

Standards

Approval and Listings Meets ANSI/TIA/EIA-568A and 606

Specifications

General Specifications	
Application	Enterprise Networks, Data Center
Mounting Type	Rack 19-in, Rack 23-in, Cabinet-mount
Product Type	Fiber Optic Hardware
Design - Hardware	
Housing Color	Black
Housing Type	CCH
Height Unit	2U
Locking Availability	Front or rear
Maximum Number of Panels per Housing	4
Panel or Module Type	CCH
Splice Tray Options	Use CCH Splice Cassette (CCH-CS)
Mechanical Characteristics	
Dimensions (HxWxD)	8.9 cm x 48.3 cm x 43 cm (3.5 in x 19 in x 17 in)

Closet Connector Housing (CCH)

2 rack units, holds 4 CCH connector panels



Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	CCH-02U
Product Description	Closet Connector Housing (CCH), 2 rack unit, holds 4 CCH connector panels

Shipping Information

Units per Delivery	1/1
--------------------	-----



Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks.

Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.

