



**SPECIFICATION**

- Housing material: PC UL 94V-0 rated, Insert material: PC UL 94V-0 rated.  
Contact Finished: 50 micro-inch gold over, Nickel 50-60 micro-inch.
- IDC Housing: PC UL 94V-0 white color.  
IDC Terminal: Phosphor Bronze, nickel plated 50-60 micro-inch.
- Jack Housing Color: Black
- P.C.B: FR4 1.6mm thickness, 2 layers.
- I.D.C CAP: PC UL 94V-0 white color.
- Certifications: ETL component ;UL listed ; ANSI/TIA/EIA-568-B.2; ISO/IEC 11801 ClassE;FCC.
- Supports: Dual T568A & T568B wiring compatible with Category 5 enhanced requirement.
- Tool : Krone · AT&T (110 Type) .
- Optional Parts : Dust cover.

**Color Colding Information**

T568B		T568A	
IDC terminal	color code	IDC terminal	color code
PIN.5	WHITE/BLUE	PIN.5	WHITE/BLUE
PIN.4	BLUE	PIN.4	BLUE
PIN.1	WHITE/ORANGE	PIN.1	WHITE/GREEN
PIN.2	ORANGE	PIN.2	GREEN
PIN.3	WHITE/GREEN	PIN.3	WHITE/ORANGE
PIN.6	GREEN	PIN.6	ORANGE
PIN.7	WHITE/BROWN	PIN.7	WHITE/BROWN
PIN.8	BROWN	PIN.8	BROWN

				<p>Unless specified on the drawing, tolerances are per the follows:</p> <p>. ±1</p> <p>.X ±0.2</p> <p>.XX ±0.05</p>
3RD				

<b>Show Me</b> CABLES				
DRAW.NO		DESC.	Cat.5e/Cat.6 90° Unshielded Keystone Jack black	
DEPARTMENT	PM	DRAW	湯欣之	DATE 06.09.14
SCALE		APPROVED	DATE	
UNIT	mm	SHEET	1 OF 1	