




FIBER PERFORMANCE	
INDUSTRY STANDARD DESIGNATION	OM1 ISO/IEC 11801
CORE/CLADDING DIAMETER (µm)	62.5/125
WAVELENGTH (nm)	850/1310
GIGABIT ETHERNET DISTANCE (M)	33/300
PRIMARY COATING DIAMETER (µm)	500
SECONDARY BUFFER DIAMETER (µm)	900

MECHANICAL AND ENVIRONMENTAL	
IMPACT RESISTANCE TIA-455-25	1500 IMPACTS
CRUSH RESISTANCE TIA-455-41	1800 N/cm
FLEX RESISTANCE TIA-455-104	2000 CYCLES
OPERATING TEMPERATURE	-55°C TO +85°C
STORAGE TEMPERATURE	-70°C TO +85°C

CABLE CHARACTERISTICS	
JACKET MATERIAL	POLYURETHANE
BUFFER MATERIAL	HARD ELASTOMERIC
CABLE DIAMETER	5 mm [.20 in]

INSTALLATION AND OPERATING CHARACTERISTICS		
	INSTALLATION	OPERATING
MAX TENSILE LOAD	1800 N [400 lbs]	600 N [130 lbs]
MIN BEND RADIUS	5 cm [2.0 in]	2.5 cm [1.0 in]

Show Me
CABLES

an INFINITE brand

Website: www.ShowMeCables.com
Phone: 1.888.519.9505



INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5

SCALE
NONE

SHEET
2 OF 2

DESCRIPTION

DEPLOYABLE MIL TACTICAL CABLE ASSY, MM, OM1, LC UPC
DUPLEX TO LC UPC DUPLEX

SIZE A	CAGE CODE 3SVT8	DRAWN BY DZINN	ITEM NO. FCA-2M1LULUMD	REV B
-----------	--------------------	-------------------	---------------------------	----------

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE. UN-DIMENSIONED/NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION. COLORS MAY VARY