

6

5

4

3

2

1

## REVISION

| ZONE | REV | DESCRIPTION     | DATE       | CHANGED BY | APPROVED   |
|------|-----|-----------------|------------|------------|------------|
|      | A   | INITIAL RELEASE | 08/01/2024 | KGLEBOVA   | NOTTINGHAM |

F

E

D

C

B

A

LENGTH  $\pm 100$  mm  
SEE LENGTH TABLE

19.69 $\pm$ 1.97  
[500 $\pm$ 50]

2X HEAT SHRINK &  
ALUMINUM TUBING

8X SC/UPC CONNECTOR

8X BREAKOUT LEADS  
2.0 mm OFNR LOOSE TUBE

4 FIBER OM1 62.5/125 CABLE  
JACKET: OFNR RISER, OD: .189 $\pm$ .008 [4.8 $\pm$ 0.2]  
COLOR: ORANGE

19.69 $\pm$ 1.97  
[500 $\pm$ 50]

## CABLE SPECIFICATIONS


| ITEM                                    | SPECIFICATION                     |
|-----------------------------------------|-----------------------------------|
| TIGHT BUFFER DIAMETER                   | .033 $\pm$ .002 [0.85 $\pm$ 0.05] |
| TIGHT BUFFER MATERIAL                   | PVC                               |
| MIN. BEND RADIUS<br>(D: CABLE DIAMETER) | 7.5D mm STATIC<br>15D mm DYNAMIC  |
| SHORT-TERM TENSILE                      | 320 N                             |
| LONG-TERM TENSILE                       | 160 N                             |
| SHORT-TERM CRUSH RESISTANCE             | 1000 N/100 mm                     |
| LONG-TERM CRUSH RESISTANCE              | 300 N/100 mm                      |
| STRENGTH MEMBER                         | ARAMID YARN                       |

## OPTICAL SPECIFICATIONS

| FIBER TYPE     | MULTIMODE     |
|----------------|---------------|
| INSERTION LOSS | $\leq 0.3$ dB |
| RETURN LOSS    | $\geq 30$ dB  |

## ITEM NUMBER

|                  | LENGTH |       |
|------------------|--------|-------|
|                  | METERS | FEET  |
| FCA-4M1CUCUR2-05 | 5.0    | 16.40 |
| FCA-4M1CUCUR2-10 | 10.0   | 32.81 |
| FCA-4M1CUCUR2-15 | 15.0   | 49.21 |



## NOTES:

- ALL CONNECTORS ACCOMPANIED WITH A DUST CAP INSTALLED (NOT SHOWN).
- CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
- CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED AND LABELED.

## REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION).

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED  
LEADING DIMENSIONS ARE INCHES  
DIMENSIONS IN [ ] ARE MILLIMETERS


TOLERANCES:  
X =  $\pm 2$  [5]  
.XX =  $\pm 0.02$  [0.5]  
.XXX =  $\pm 0.005$  [0.13]  
FRACTIONS  
 $\pm 1/32$   
ANGLES  $\pm 1^\circ$

CABLE LENGTH TOLERANCES:  
 $\leq 12$  [305] =  $\pm 1$  [25] / -0  
 $>12$  [305]  $\leq 60$  [1524] =  $\pm 2$  [51] / -0  
 $>60$  [1524]  $\leq 120$  [3048] =  $\pm 4$  [102] / -0  
 $>120$  [3048]  $\leq 300$  [7620] =  $\pm 6$  [152] / -0  
 $>300$  [7620] =  $\pm 5\%$  / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY  
AND SUBJECT TO CHANGE WITHOUT NOTICE.  
UN-DIMENSIONED/NON-CRITICAL FEATURES  
MAY VARY IN SIZE AND LOCATION  
COLORS MAY VARY

**Show Me**  
CABLES  
an INFINITE brand

Website: [www.ShowMeCables.com](http://www.ShowMeCables.com)  
Phone: 1.888.519.9505



INTERPRET ALL DIMENSIONS AND  
TOLERANCES PER ASME Y14.5

SCALE  
NONE

SHEET  
1 OF 1

## DESCRIPTION

FIBER DIST CABLE, 4 STRAND SC/UPC-SC/UPC OM1, 4.8 mm  
RISER JKT, 2.0 mm BREAKOUT AT .5M

| SIZE | CAGE CODE | DRAWN BY | ITEM NO.      | REV |
|------|-----------|----------|---------------|-----|
| A    | 3SVT8     | KGLEBOVA | FCA-4M1CUCUR2 | A   |

6

5

4

3

2

1