





THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	10/18/2022	PHOSPODAR

LENGTH	
LENGTH (L) METER [FEET]	TOLERANCE MM [INCHES]
5 [16.40]	+50/-0 [+1.97/0]
10 [32.81]	+100/-0 [+3.94/0]
20 [65.62]	+1%*L/-0
30 [98.43]	+1%*L/-0



OPTICAL SPECIFICATION	
FIBER TYPE	MULTIMODE
CONNECTOR TYPE	IP-MPO/UPC
INSERTION LOSS	≤ 0.5dB
RETURN LOSS	≥ 25dB
TEST WAVE LENGTH	850 & 1300nm



NOTES:

1. MPO POLARITY: TIA METHOD B.
2. ALL CONNECTORS INCLUDE PROTECTIVE DUST CAPS.
3. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IAW L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]		APPROVALS	DATE	 an INFINITI® brand 50 High Street, West Mill, North Andover, MA 01845 USA. Phone: 1.800.341.5266 1.978.682.6936
OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0		DRAWN BY DZINN	10/18/2022	
ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 [5] .XX = ± .02 [.5] .XXX = ± .005 [.13]		CHECKED BY DMAY	10/18/2022	
THIRD-ANGLE PROJECTION 		APPROVED BY REVANGELIS	10/18/2022	
CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		CATEGORY FIBER OPTIC		PRODUCT DESCRIPTION IP68 OUTDOOR CABLE ASSY, 5MM OD OM4, MPO/UPC MALE 12F TO MPO/UPC MALE 12F, TYPE B
COLOR VARIATIONS MAY OCCUR		SIZE A	CAGE CODE 43321	
		ITEM NO. FOCM4ODMPMB12	REV. A	
		SCALE: NONE	CAD FILE: FOCM4ODMPMB12.SLDDRW	SHEET 1 OF 1