



| WIRING MAP | | |
|------------|--------|------|
| "P1" | COLOR | "P2" |
| 1 | WHITE | 1 |
| 2 | BLACK | 2 |
| 3 | RED | 3 |
| 4 | GREEN | 4 |
| 5 | YELLOW | 5 |
| 6 | BLUE | 6 |

NOTES:

MATERIAL:

PLUG HOUSING: POLYCARBONATE, CLEAR, UL94V-0
 CONTACTS: PHOSPHOR BRONZE
 JACKET: PVC DOUBLE SHIELDED WITH FOIL AND BRAID SHIELD

FINISH:

CONTACTS: 50 μINCHES GOLD IN CONTACT AREA
 OVER 100 μINCHES NICKEL PLATE OVERALL.

CABLE CHARACTERISTICS:

6 CONDUCTOR ROUND CABLE, SHIELDED
 U.L. STYLE 20251, 26 AWG STRANDED

UNLESS OTHERWISE SPECIFIED,
 DIMENSIONS ARE IN INCHES (mm)

TOLENCANCES TO BE:
 .X ± .1 (2.5) ANGLES ±2°
 .XX ± .01 (.25)
 .XXX ± .005 (.13)



| | | | | | |
|-----------------------------|----------|-------------------------|------|--------------|--|
| CATEGORY | | | | MODULAR | |
| PRODUCT DESCRIPTION | | | | | |
| ROUND CABLE, (6X6) STRAIGHT | | | | | |
| SIZE | TSCM NO. | DWG. NO. | REV. | | |
| A | 43321 | TDC057 | C | | |
| SCALE: NONE | | CAD FILE: TDC007.SLDRAW | | SHEET 1 OF 1 | |