



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SHOW ME CABLES, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SHOW ME CABLES, INC. IS PROHIBITED.

REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	04/04/2023	SREITER	GUTTADAURO




WIRING DIAGRAM



PART NUMBER	LENGTH	
	FEET	METERS
M83PVC-MF-1M	3.3	1
M83PVC-MF-3M	9.8	3
M83PVC-MF-5M	16.4	5

NOTES:

- 100% OPEN, SHORT, MISWIRE TEST
- INSULATION RESISTANCE: 10MΩ MIN, 300VDC;
CONDUCTOR RESISTANCE: 3Ω MAX
- WATERPROOF IP67
- LEAD-FREE SOLDER TIN
- OPERATING TEMPERATURE RANGE: -20°C~80°C
- CABLE ASSEMBLIES TO BE TESTED FOR CONTINUITY.
- CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]		APPROVALS		DATE		Show Me CABLES an INFINITI® brand		115 Chesterfield Industrial Blvd., Chesterfield, MO 63005 Phone: 1.888.519.9505 Fax: 1.888.519.9515	
OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0 ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 [5] FRACTIONS .XX = ± .02 [.5] ± 1/32 .XXX = ± .005 [.13] ANGLES ± 1°		DRAWN BY SREITER		04/04/2023					
		CHECKED BY DGUST		04/05/2023					
		APPROVED BY GUTTADAURO		04/05/2023					
THIRD-ANGLE PROJECTION 		CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		CATEGORY CABLE ASSEMBLY		PRODUCT DESCRIPTION SHOWMECABLES M8 3 POSITION CABLE, PVC JACKET, MALE/FEMALE - 1M			
		COLOR VARIATIONS MAY OCCUR		SIZE A	CAGE CODE 3SVT8	ITEM NO. M83PVC-MF-1M	REV. A		
				SCALE: NONE		CAD FILE: M83PVC-MF-1M.SLDDRW		SHEET 1 OF 1	