

Show Me

CABLES

cables & connectors since 1995

Category 6 550MHz Plenum

ETL verified for guaranteed performance
Made in the USA

Applications

Supports all Gigabit Ethernet/1000BASE-T/IEEE 802.3ab, ATM up to 155 Mbps, 100 Mbps Fast Ethernet 100BASE-T/IEEE 802.3, ANSI.X3.263 FDDI TP-PMD, Ethernet 10BASE-T/IEEE 802.5, T1/E1, xDSL, ISDN, 550 MHz Broadband Video and standards under development such as ATM at 622 Mbps, 1.2, 2.4 and 4.8 Gbps

Construction Details:


No. 23 AWG copper conductor insulated with FEP. Two colored mated insulated conductors twisted together to form a pair and four pairs assembled to form a core. The core is jacketed with a low smoke flame retardant PVC.

Color Code:

Pair	Color Code
1	Blue with White
2	Orange with White
3	Green with White
4	Brown with White

Electrical Parameters:

Mutual Capacitance:	14 pF/ft nominal
Capacitance Unbalance:	330 pF/ft maximum
Velocity of Propagation:	72%
Max. Conductor D.C.R.:	28.6 ohm/1000 feet
Max. DCR Unbalance:	5%
Max. Delay Skew:	45.0 ns/100m
Characteristic Impedance:	from 0.772 - 100 MHz $100 \pm 15\%$ from 100 - 250 MHz $100 \pm 22\%$ from 201 - 550 MHz $100 \pm 32\%$



Technical Details

Temperature Rating	
Installation:	0°C to 50°C
Operation:	-10°C to 60°C
Nominal Diameter:	0.230 in.
Nominal Cable Weight:	37 lbs/1,000 feet

Standards

- ANSI/TIA/EIA 568C.2 Category 6
- National Electric Code – Article 800

Codes & Listings

- CMP rating FT6
- ETL Electrically Verified to ANSI/TIA/EIA 568C.2 Category 6
- C(ETL)US CMP



Issue Date: 06/11
Revision: 2

This product is RoHS compliant to directive 2002/95/EC .

It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.

Show Me

CABLES

cables & connectors since 1995

Category 6 550MHz Plenum

ETL verified for guaranteed performance
Made in the USA

Electrical Characteristics:

Frequency	Return Loss	Attenuation	NEXT	PS-NEXT	ELFEXT	PS-ELFEXT	ACR	PS-ACR
	dB	dB(100m)	dB	dB	dB	dB	dB	dB
MHz	Minimum	Maximum	Minimum	Minimum	Minimum	Minimum	Minimum	Minimum
1	20.0	2.0	80.3	78.3	73.8	70.8	78.3	76.3
4	23.0	3.8	71.3	69.3	61.8	58.8	67.5	65.5
10	25.0	6.0	65.3	63.3	53.8	50.8	59.3	57.3
16	25.0	7.6	62.2	60.2	49.7	46.7	54.6	52.6
20	25.0	8.5	60.8	58.8	47.8	44.8	52.3	50.3
31.25	23.6	10.7	57.9	55.9	43.9	40.9	47.2	45.2
62.5	21.5	15.4	53.4	51.4	37.9	34.9	38.0	36.0
100	20.1	19.8	50.3	48.3	33.8	30.8	30.5	28.5
200	18.0	29.0	45.8	43.8	27.8	24.8	16.8	14.9
250	17.3	32.8	44.3	42.3	25.8	22.8	11.5	9.5
300	16.8	36.4	43.1	41.1	24.3	21.3	----	----
350	16.3	39.8	42.1	40.1	22.9	19.9	----	----
400	15.9	43.0	41.3	39.3	21.8	18.8	----	----
500	14.8	49.5	40.2	38.2	20.0	17.0	----	----
550	14.4	53.1	39.5	37.5	18.9	15.9	----	----

*Values above 250 MHz are for engineering information only

Preparation For Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



MADE IN THE USA



Issue Date: 06/11
Revision: 2

This product is RoHS compliant to directive 2002/95/EC .

It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.