

## 14x12x6" UL® Listed Polycarbonate Weatherproof NEMA 4X Enclosure, Dark Gray

### NBPC141206



#### Features

- UL® Listed High-Impact, UV Resistant Polycarbonate (Dark Gray)
- Stainless steel latches with padlock eye
- NEMA Type 4X / IP66\* rated (includes (4x) optional lid corner screws\*\*)
- Fully gasketed lid & user installed wall mounting brackets

#### Applications

- Remote Wireless LAN WiFi equipment installations
- Indoor and outdoor installations
- Rapid Deployment Installations
- Corrosive environments & hotspot applications
- Protection of equipment from theft or damage

#### Description

The box is a rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from High-Impact, UV Resistant Polycarbonate material that provides superior durability to impacts and ease of modification while maintaining minimum weight. It is well suited for high temperature or corrosive environments. The included wall mount brackets come uninstalled and bagged with their hardware inside of the enclosure. Once the brackets are installed the enclosure can be mounted directly to any flat wall surface provided proper screws are used into secure studs. The brackets, once installed, also allow you to use our HGX-PMT pole mount kits. The lid features a non-metallic hinge system that allows for quick removal & can be reattached just as quickly without the need for any tools. The enclosure comes with a pair of stainless-steel latches with padlock eyes allowing you to secure the enclosure from tampering. The enclosure comes in a Dark Gray (Pantone 422C)

The HGX-PMT series of pole mounting kits allow the populated enclosure to be securely mounted to a variety of different size poles.

Compatible versions include HGX-PMT13, HGX-PMT16, HGX-PMT28, HGX-PMT29, HGX-PMT30, & HGX-PMT33

\*Note: Any holes or openings you might introduce must be properly sealed to maintain NEMA Type 4X / IP66 rating

\*\*Note: If all four of the optional lid screws are installed the enclosure can achieve NEMA 6P / IP68 however any holes or openings you may have added would have to be properly sealed with an IP68 rated plug, gland or coupler.

#### Mechanical Specifications

##### Size

|                    |               |             |
|--------------------|---------------|-------------|
| Outer Height       | 14.6 in       | [370.84 mm] |
| Outer Width        | 12.6 in       | [320.04 mm] |
| Outer Depth        | 7.4 in        | [187.96 mm] |
| Inner Height       | 13.7 in       | [347.98 mm] |
| Inner Width        | 11.7 in       | [297.18 mm] |
| Inner Depth        | 5.9 in        | [149.86 mm] |
| Weight             | 9 lbs         | [4.08 kg]   |
| Enclosure Material | Polycarbonate |             |

#### Environmental Specifications

|                                |                               |
|--------------------------------|-------------------------------|
| Temperature Rating             | -40° to 265°F [-40° to 129°C] |
| NEMA Rating                    | 4X                            |
| Ingress Protection (IP) Rating | IP66                          |

#### Compliance Certifications

|           |         |
|-----------|---------|
| UL Listed | E508536 |
|-----------|---------|

## 14x12x6" UL® Listed Polycarbonate Weatherproof NEMA 4X Enclosure, Dark Gray

### NBPC141206



14x12x6" UL® Listed Polycarbonate Weatherproof NEMA 4X Enclosure, Dark Gray from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

URL: <https://www.l-com.com/nema-enclosures-14x12x6-ul-listed-polycarbonate-weatherproof-nema-4x-enclosure-dark-gray-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.