

6

5


4

3

2

1

REVISION				
ZONE	REV	DESCRIPTION	DATE	CHANGED BY
	B	UPDATED PER ECO-13673	06/25/2024	HBAKKE
				APPROVED
				DGUST



NOTES:

PHYSICAL:

- CONDUCTOR TYPE: 22AWG, STRANDED TC.
- INSULATION: HDPE.
- CONDUCTOR DIA: $1.5 \pm 0.05\text{mm}$.
- CONNECTOR: 50U" GOLD PLATED.
- MINIMUM AVERAGE CABLE THICKNESS: .026 [0.65].

ELECTRICAL:

- BANDWIDTH: 100 MHz.
- NOMINAL VOLTAGE RATING: 30 V.
- RESISTANCE: $7.08\Omega/100\text{m}$ (MAXIMUM).
- IMPEDANCE: 100Ω .
- CAPACITANCE: $5600\text{pf}/100\text{m}$.
- PROPAGATION DELAY: $545\text{ns}/100\text{m}$ (MAXIMUM).
- DELAY SKEW: $45\text{ns}/100\text{m}$ (MAXIMUM).
- PASS FLUKE DSX 8000 CHANNEL TEST.

ENVIRONMENTAL:

- INSTALLATION TEMPERATURE RANGE: 0°C TO $\sim 50^{\circ}\text{C}$
- OPERATING TEMPERATURE RANGE: -40°C TO $\sim 80^{\circ}\text{C}$

MISCELLANEOUS

- CABLE ASSEMBLY TO BE TESTED FOR CONTINUITY.
- CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED.

REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENTLY RELEASED VERSION).

P1	WIRE MAP	P2
YELLOW 1		1 YELLOW
ORANGE 2		2 ORANGE
WHITE 3		3 WHITE
BLUE 6		6 BLUE
SHIELDED S		S SHIELDED

ITEM NO	LENGTH [TOL.]	
	METERS [mm]	FEET [IN]
PC506-05M	0.5 [+35/-15]	1.64 [+1.38/- .59]
PC506-1M	1 [+35/-20]	3.28 [+1.38/- .79]
PC506-2M	2 [+35/-30]	6.56 [+1.38/-1.18]
PC506-3M	3 [+35/-30]	9.84 [+1.38/-1.18]
PC506-5M	5 [± 60]	16.40 [± 2.36]
PC506-10M	10 [± 80]	32.81 [± 3.15]

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

6

5

4

3

2

1

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS	
TOLERANCES:	
X = ± 2 [5]	FRACTIONS $\pm 1/32$
.XX = ± 0.02 [0.5]	ANGLES $\pm 1^{\circ}$
.XXX = ± 0.005 [0.13]	
CABLE LENGTH TOLERANCES:	
≤ 12 [305] = ± 1 [25] / -0	
>12 [305] ≤ 60 [1524] = ± 2 [51] / -0	
>60 [1524] ≤ 120 [3048] = ± 4 [102] / -0	
>120 [3048] ≤ 300 [7620] = ± 6 [152] / -0	
>300 [7620] = $\pm 5\%$ / -0	
ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE. UN-DIMENSIONED/NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION COLORS MAY VARY	

Show Me
CABLES
an INFINIT® brand

Website: www.ShowMeCables.com
Phone: 1.888.519.9505



INTERPRET ALL DIMENSIONS AND
TOLERANCES PER ASME Y14.5

SCALE
NONE

SHEET
1 OF 1

DESCRIPTION
PROFINET C5e 2P RJ45 SF/UTP 22STR PUR GRN

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	3SVT8	KGLEBOVA	PC506	B