

413 to 423 MHz Rubber Duck Antenna SMA Male



SMANRBD1069

Features

- 413 MHz to 423 MHz
- SMA Male connector
- VSWR 2:1
- Linear polarization

Applications

- LPWAN
- ISM
- Weightless-P
- Fixed and Mobile Devices

Description

The SMANRBD1069 is a high-quality single-band rubber duck antenna with a frequency range of 413 MHz to 423 MHz. ShowMeCables's omnidirectional rubber duck antenna is 2 inches tall and 0.37 inches wide.

The SMANRBD1069 rubber duck antenna from ShowMeCables features a SMA Male connector with an input VSWR (voltage standing wave ratio) of 2:1.

ShowMeCables's linearly polarized antenna can operate at temperatures ranging from -40 °C to 60 °C. This single-band rubber duck antenna is offered with expert technical support, PDF datasheets, and CAD drawings with dimensions and specifications.

Configuration

Design	Rubber Duck
Band Type	Single
Radiation Pattern	Omni Directional
Polarization	Linear
Connector Type	SMA Male
Number of Ports	1

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	413		423	MHz
Center Frequency		418		MHz
Input VSWR			2:1	
Impedance		50		Ohms

Mechanical Specifications

Radome Material	ABS
-----------------	-----

Size

Length	2 in [50.8 mm]
Width	0.37 in [9.4 mm]
Height	0.37 in [9.4 mm]
Weight	0.2 lbs [90.72 g]

413 to 423 MHz Rubber Duck Antenna SMA Male



SMANRBD1069

Environmental Specifications

Temperature

Operating Range

-40 to +60 deg C

Storage Range

-40 to +80 deg C

Ingress Protection

IP65

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Radiation Pattern

Appendix

Electrical Downtilt: Angle in the antenna's elevation pattern in which the maximum gain occurs.

Gain: Antenna's average gain.

Front to Back Ratio @ 180°±30°: Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

Cross-polarization Ratio (dB): Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

FPO Show Me Cables specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

FPO Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [413 to 423 MHz Rubber Duck Antenna SMA Male SMANRBD1069](#)

FPO The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Show Me Cables reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Show Me Cables does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Show Me Cables does not assume liability arising out of the use of any part or document.

413 to 423 MHz Rubber Duck Antenna SMA Male

