

## 2.4 to 7.125 GHz Rubber Duck Antenna SMA Male Tilt Swivel



### SMANRBD1072

#### Features

- 2400 MHz to 7125 MHz
- 3 dBi Gain
- SMA Male connector
- Tilt/Swivel
- VSWR 3.5:1
- Linear polarization

#### Applications

- WLAN
- WiFi 6E
- WiFi 6
- WiFi 5
- WiFi 4
- U-NII 1-4, 5-8
- 802.11b/g/n/ac
- Fixed and Mobile Devices

#### Description

The SMANRBD1072 is a high-quality multi-band rubber duck antenna with 3 dBi nominal gain and has a frequency range of 2400 MHz to 7125 MHz. ShowMeCables's omnidirectional tilt/swivel rubber duck antenna is 2.81 inches tall and 0.4 inches wide.

The SMANRBD1072 rubber duck antenna from ShowMeCables features a SMA Male connector with an input VSWR (voltage standing wave ratio) of 3.5:1.

ShowMeCables's linearly polarized antenna can operate at temperatures ranging from -40 °C to 60 °C. This multi-band rubber duck antenna is offered with expert technical support, PDF datasheets, and CAD drawings with dimensions and specifications.

#### Configuration

Design	Rubber Duck
Band Type	Multi
Radiation Pattern	Omni Directional
Polarization	Linear
Connector Type	SMA Male
Number of Ports	1

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	2,400		7,125	MHz
Input VSWR			3.5:1	
Impedance		50		Ohms
Gain		3		dBi

#### Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Frequency	2.4 to 2.5	5.15 to 5.85	5.925 to 7.125			GHz

#### Mechanical Specifications

Radome Material	ABS
Size	
Length	2.81 in [71.37 mm]

## 2.4 to 7.125 GHz Rubber Duck Antenna SMA Male Tilt Swivel



### SMANRBD1072

Width	0.4 in [10.16 mm]
Height	0.04 in [1.02 mm]
Weight	0.2 lbs [90.72 g]

#### Environmental Specifications

<b>Temperature</b>	
Operating Range	-20 to +70 deg C
Storage Range	-20 to +80 deg C

**Compliance Certifications** (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

#### Typical Radiation Pattern

#### Appendix

**Electrical Downtilt:** Angle in the antenna's elevation pattern in which the maximum gain occurs.

**Gain:** Antenna's average gain.

**Front to Back Ratio @ 180°±30°:** Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

**Cross-polarization Ratio (dB):** Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

**FPO** Show Me Cables specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

**FPO** Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4 to 7.125 GHz Rubber Duck Antenna SMA Male Tilt Swivel SMANRBD1072](#)

**FPO** The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Show Me Cables reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Show Me Cables does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Show Me Cables does not assume liability arising out of the use of any part or document.

SMANRBD1072 CAD Drawing

2.4 to 7.125 GHz Rubber Duck Antenna SMA Male Tilt Swivel

