

# 2 Watt RF Termination 50 Ohm BNC Female, DC to 4 GHz



# **SMTR6256**

#### **Features**

- · DC to 4GHz Frequency Range
- 50 Ohm Impedance
- VSWR 1.2:1 Max

#### **Applications**

- Wireless
- · Video Signal Transmission
- Radar Systems

- Max Power 2 Watts (CW)
- · BNC Female Coaxial Interface
- Test and Measurement
- · Commercial and Military Communication
- Avionics

## **Description**

ShowMeCables's SMTR6256 is an RF termination (also called RF load or dummy load) that operates from DC to 4 GHz and handles up to 2 Watt (CW). Our BNC termination / load has a female gender. SMTR6256 BNC load termination offers 1.2:1 max VSWR. RF load / terminations are indispensable components in many RF, microwave and millimeter wave systems where signal reflection from unused ports can potentially damage the device or reduce the signal integrity. By using a terminator on an unused port with a matched load (dummy load), the incident energy will be absorbed with minimal reflection. These termination components are commonly used to terminate devices such as couplers, circulators, and switches. They are also widely used in measurement systems to ensure accurate results. ShowMeCables offers a huge selection of RF, microwave and millimeter wave terminations up to 18 GHz with excellent performance over the entire operating range.

#### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		4	GHz
Impedance		50		Ohms
VSWR, Input			1.2:1	
Input Power (CW)			2	Watts

### **Mechanical Specifications**

Size

 Length
 0.9 in [22.86 mm]

 Width
 0.433 in [11 mm]

 Weight
 0.024 lbs [10.89 g]

 Package Type
 Connectorized

Configuration

Connector BNC Female Connector Specification MIL-STD-348

## **Material Specifications**

Description	Material	Plating
Insulation	Teflon	
Connector 1 Body	Brass	Tri-Metal
Housing	Brass	Tri-Metal



# 2 Watt RF Termination 50 Ohm BNC Female, DC to 4 GHz



# **SMTR6256**

#### **Environmental Specifications**

**Temperature** 

Compliance Certifications (see product page for current document)

#### **Plotted and Other Data**

Notes:

**FPO** Show Me Cables specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

**FPO** Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2 Watt RF Termination 50 Ohm BNC Female, DC to 4 GHz SMTR6256

URL: https://www.showmecables.com/showmecables-2-watt-rf-load-up-to-4-ghz-with-bnc-male-p.aspx

**FPO** The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Show Me Cables reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Show Me Cables does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Show Me Cables does not assume liability arising out of the use of any part or document.

