


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	06/15/2023	SREITER	GUTTADAURO


1. CONSTRUCTION:
 1. ASSEMBLY: 1 PAIR COMPONENT A, 2 CORES COMPONENT B
 2. JACKET:
 1. MATERIAL: TPU
 2. OVERALL DIAMETER: 6.5 ± 0.30 mm
 3. THICKNESS: MIN. 0.50 mm
 4. COLOR: GREEN
 3. COMPONENT A (DATA):
 1. CONDUCTOR: BARE COPPER WIRE 7/ 0.16 ± 0.008 mm (26 AWG)
 2. INSULATION: FOAM PE
 3. DIELECTRIC CORE OD: 1.06 ± 0.05 mm
 4. FILLER: PE FILLER
 5. SHIELD: AL-PET (NOM. 25% OVERLAP, AL SIDE FACE-OUT) TINNED COPPER WIRE BRAIDING (NOM. 85% COVERAGE)
 6. COLOR CODE:
 1. WHITE / BLUE
 4. COMPONENT B (DATA):
 1. CONDUCTOR: BARE COPPER WIRE 19/ 0.25 ± 0.008 mm (18 AWG)
 2. INSULATION: PP
 3. DIELECTRIC CORE OD: 1.65 ± 0.05 mm
 4. FILLER: PE FILLER / ARAMID YARN
 5. SHIELD: AL-PET (NOM. 25% OVERLAP, AL SIDE FACE-OUT) TINNED COPPER WIRE BRAIDING (NOM. 90% COVERAGE)
 6. COLOR CODE:
 2. RED
 3. BLACK



CROSS-SECTIONAL
VIEW

CABLE LENGTH		
PART NO.	FEET	METERS
TSPEH02-05M	16.4	5
TSPEH02-10M	32.8	10

2. MECHANICAL PROPERTIES:
 1. BEND RADIUS:
 1. $\geq 4X$ OD WITHOUT LOAD
 2. $\geq 8X$ OD WITH LOAD
 2. TEMPERATURE RANGE:
 3. DURING OPERATION: -40°C UP TO 80°C
 4. DURING INSTALLATION: 0°C UP TO 50°C

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0 ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 [5] FRACTIONS ± 1/32 .XX = ± .02 [.5] ANGLES ± 1° .XXX = ± .005 [.13]	APPROVALS	DATE	L-com™ an INFINITI® brand		50 High Street, West Mill, North Andover, MA 01845 USA. Phone: 1.800.341.5266 1.978.682.6936	
	DRAWN BY SREITER	06/15/2023				
	CHECKED BY DGUST	06/15/2023	CATEGORY			
	APPROVED BY GUTTADAURO	06/15/2023	BULK CABLE			
CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY			PRODUCT DESCRIPTION SINGLE PAIR ETHERNET HYBRID (SPE) BULK SF/TP 26AWG STRANDED DATA PAIR + 2X18AWG POWER, TPU GREEN, PER METER			
THIRD-ANGLE PROJECTION 	COLOR VARIATIONS MAY OCCUR		SIZE A	CAGE CODE 43321	ITEM NO. TSPEH02	REV. A
			SCALE: NONE CAD FILE: TSPEH02.SLDDRW			SHEET 1 OF 2


8 7 6 5 4 3 2 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE
PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE
WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	06/15/2023	SREITER	GUTTADAURO

1. TRANSMISSION PERFORMANCE ACC. TO IEC 61156-12 (AT 20°C / 100 m):

	FREQUENCY	IMPEDANCE (Ω)	INSERTION LOSS (dB) MAX.	RETURN LOSS (dB) MIN.	PROPAGATION DELAY (ns) MAX.
1.	1	100 ±15	3.1	20.0	570
2.	4	100 ±15	5.6	23.0	552
3.	10	100 ±15	8.7	25.0	545
4.	16	100 ±15	11.0	25.0	543
5.	20	100 ±15	12.2	25.0	542
6.	31.25	100 ±15	15.5	23.2	541
7.	62.5	100 ±15	21.8	20.8	538
8.	100	100 ±15	27.8	19.0	538
9.	125	100 ±15	31.2	18.2	537
10.	200	100 ±15	39.7	16.4	537
11.	250	100 ±15	44.6	15.6	536
12.	300	100 ±15	49.0	15.6	536
13.	500	100 ±15	64.1	15.6	536
14.	600	100 ±15	70.7	15.6	536
15.					

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]		APPROVALS		DATE		L-com[™] an INFINITI® brand		50 High Street, West Mill, North Andover, MA 01845 USA. Phone: 1.800.341.5266 1.978.682.6936			
OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0 ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 [5] FRACTIONS .XX = ± .02 [.5] ± 1/32 .XXX = ± .005 [.13] ANGLES ± 1° THIRD-ANGLE PROJECTION 		DRAWN BY SREITER		06/15/2023						CATEGORY BULK CABLE	
		CHECKED BY DGUST		06/15/2023							
		APPROVED BY GUTTADAURO		06/15/2023							
		CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		PRODUCT DESCRIPTION SINGLE PAIR ETHERNET HYBRID (SPE) BULK SF/TP 26AWG STRANDED DATA PAIR + 2X18AWG POWER, TPU GREEN, PER METER		SIZE		CAGE CODE		ITEM NO.	
						A		43321		TSPEH02	
COLOR VARIATIONS MAY OCCUR		SCALE: NONE		CAD FILE: TSPEH02.SLDDRW		REV. A		SHEET 2 OF 2			